

Hazardous Substance, Non-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product Name Ultimate 2 Pack Epoxy Satin White, Tint Bases And

Milled Colours (Parts A & B).

Product Code : U2ES, U2ESH

Product Use: Two-pack water-based epoxy coating.

Company Name: Haymes Paint ABN: 14 004 201 638

Address: Waringa Drive, Wendouree Industrial Park, Victoria 3355, Australia. Emergency Telephone: 03 5342 6200. Office Hours: 7:30am to 5:30pm Monday to Friday.

Poisons Information Centre: 13 11 26 (From anywhere and anytime in Australia)

Tel: 03 5342 6200. Office Hours: 7:30am to 5:30pm Monday to Friday.

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



SIGNAL WORD: Warning

Hazard Classification : Skin Irritation - Catergory 2

Skin Sensitisation - Category 1A Eye Irritation - Category 2A

Hazard Statement(s): H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

Precautionary Statement(s):

Prevention: P102: Keep out of reach of children.

P103: Read label before use.

P261: Avoid breathing fumes, mists, vapours or spray. P262: Do not get in eyes, on skin, or on clothing. P264: Wash contacted areas thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace. P280: Wear protective gloves, protective clothing and eye or face protection.

Response: P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice. P337+P313: If eye irritation persists: Get medical advice.

Product name: Ultimate 2 Pack Epoxy Satin White, Tint Bases And Milled Colours (Part A)

 Issued:
 29-9-22

 Version:
 2.2

 Page 1 of 7



Storage: P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container. P403+P235: Store in a well-ventilated place. Keep cool.

Disposal: P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and

containers to landfill.

SUSMP Poisons Schedule: Not Scheduled.

3. COMPOSITION INFORMATION

Chemical Entity

Bisphenol A, (chloromethyl) oxirane polymer

25068-38-6

30-60 %

Ingredients determined not to be hazardous:

- Balance
100%

4. FIRST AID MEASURES

For advice, contact a doctor or the Poisons Information Centre (Phone Australia 13 11 26).

Inhalation : No first aid measures normally required. However, if inhalation has occurred, and irritation

has developed, remove to fresh air and observe until recovered. If irritation becomes

painful or persists more than about 30 minutes, seek medical advice.

Skin: Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-

20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely

decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek

medical attention.

Eye: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15

minutes or until the product is removed, while holding the eyelid(s) open. Take care not to

rinse contaminated water into the unaffected eye or onto the face. Obtain medical

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and give some water to

drink. If symptons develop, or in doubt, contact a Poisons Information Centre or a doctor.

First Aid Facilities: Emergency eye wash facility.

Advice to Doctor : Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Hazchem Code : Not Applicable.

Suitable extinguishing media: Not combustible, however, if material is involved in fire use extinguishing media

appropriate to surrounding fire conditions.

Specific hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or

both), fire gases. There is no risk of an explosion from this product under normal

circumstances if it is involved in a fire. Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness. Fire decomposition products from this product may be irritating if

inhaled. Take appropriate protective measures.

Product name: Ultimate 2 Pack Epoxy Satin White, Tint Bases And Milled Colours (Part A)

Issued: 29-9-22 Version: 2.2

Page 2 of 7



Fire fighting further advice : Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if

risk of exposure to products of decomposition. Prevent any possible contamination of

drains and waterways.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of

vapours. Collect and seal in properly labelled containers or drums for disposal.

Large Spills: Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so.

Avoid accidents, clean up immediately. Wear full protective chemically resistant equipment to prevent skin and eye contamination and the inhalation of any vapours or dust. Work up wind or increase ventilation. Contain - prevent any possible contamination of drains and waterways. Collect and seal in properly labelled containers or drums for disposal. If contamination of drains or waterways has occurred advise local emergency services.

7. HANDLING AND STORAGE

Persons sensitised to Bisphenol A, (chloromethyl) oxirane polymer should avoid contact with this product.

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work

areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product

Storage: Make sure that containers of this product are kept tightly closed. Keep containers dry and

away from water. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further

storage instructions on the label.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control Parameters: Exposure limits have not been established by SWA for any of the significant ingredients in

this product.

Chemical Entity TWA STEL Carcinogen Category Notices

ppm mg/m3 ppm mg/m3

Limits not established

As published by Safe Work Australia

TWA - the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15-minute period, which should not be expected at any time during a normal eight-hour workday.

"Sk" Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If directions for use are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Product name: Ultimate 2 Pack Epoxy Satin White, Tint Bases And Milled Colours (Part A)

Issued: 29-9-

Version: 2.2 Page 3 of 7



Engineering Controls: Ensure ventilation is adequate and that air concentrations are controlled below quoted

Workplace Exposure Standards. Close with lid when not in use.

Personal

protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES

Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid supplied in a variety of colours.

Odour :No data re odour.Solubility :Miscible in water.

Specific Gravity (20 degC): 1.4

Relative Vapour Density (air=1): As for water.

Vapour Pressure (20degC): 2.37 kPa at 20°C (water vapour pressure).

Flammability Limits (%):

Autoignition Temperature (degC):

Not Applicable

Not Applicable

Melting Point/Range (degC): No specific data. Liquid at normal temperatures.

Boiling Point/Range (degC):

As for water (100°C)

PH:

Not Available

Viscosity: Not Available
Total VOC (g/litre): Not Available

(Typical values only)

N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: This product is unlikely to react or decompose under normal storage conditions.

However, if you have any doubts, contact the supplier for advice on shelf life

properties.

Chemical stability: Stable under normal ambient and anticipated storage and handling conditions of

temperature and pressure.

Hazardous reactions : This product will not undergo polymerisation reactions.

Conditions to avoid : Keep containers tightly closed. Containers should be kept dry.

Incompatible materials: Strong acids, strong bases, strong oxidising agents.

Hazardous decomposition products : This product is likely to decompose only after heating to dryness, followed by

further strong heating. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form hydrogen

chloride gas, other compounds of chlorine.

Product name: Ultimate 2 Pack Epoxy Satin White, Tint Bases And Milled Colours (Part A)

Issued: 29-9-22

Version: 2.2 Page 4 of 7



11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if material is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute effects:

Inhalation : Available data indicates that this product is not harmful. However product may be mildly

irritating, although unlikely to cause anything more than mild transient discomfort.

Skin contact : Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once

sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become

evident, but all should disappear once exposure has ceased.

Ingestion: This product is a severe eye irritant. Symptoms may include stinging and reddening of eyes

and watering which may become copious. Other symptoms such as swelling of eyelids and blurred vision may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment is likely to

Eye contact: Significant oral exposure is considered to be unlikely. However, this product is an oral

irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure

has ceased.

Acute toxicity:

Inhalation :No information available.Skin contact :No information available.Ingestion :No information available.

Skin corrosion/irritation: This product has been classified as a Catergory 2 Hazard. Causes skin irritation.

Serious eye damage/irritation : This material has been classified as a Category 2A Hazard. Causes serious eye irritation.

Respiratory Sensitisation : No information available.

Skin Sensitisation : This product has been classified as a Category 1A Hazard - skin sensitiser.

Chronic Toxicity:

Mutagenicity:No information available.Carcinogenicity:No information available.Reproductive toxicity:No information available.

Specific target organ toxicity

(single exposure): No information available.

Specific target organ toxicity

(repeat exposure):

No information available.

Aspiration hazard : No information available.

Product name: Ultimate 2 Pack Epoxy Satin White, Tint Bases And Milled Colours (Part A)

Issued: 29-9-22

Version: 2.2 Page 5 of 7



12. ECOLOGICAL INFORMATION

Avoid contaminating drains and waterways.

Ecotoxicity: Harmful to aquatic organisms, may cause long-term adverse effects to the aquatic

environment.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled dispose in accordance with local, regional, national and international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport : Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport

of Dangerous Goods by Road and Rail". NON DANGEROUS GOODS.

Marine Transport: Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous

Goods Code (IMDG) Code) for transport by sea. NON DANGEROUS GOODS.

Air Transport : Not classified as Dangerous Goods by the criteria of the International Air Transport

Association (IATA) Dangerous Goods Regulations for transport by air. NON DANGEROUS

GOODS.

15. REGULATORY INFORMATION

This product/constituent(s) is/are covered by the following requirements :

This material is hazardous according to health criteria of Safe Work Australia. HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road and Rail". NON DANGEROUS GOODS.

The Standard for the Uniform Scheduling of Medicines and Poisons No. 36. Not Scheduled.

All the constituents of this product are listed on the Australian Inventory of Industrial Chemicals (AIIC), or exempted.

16. OTHER INFORMATION

This product is not manufactured by Haymes Paint. This Safety Data Sheet is prepared from proprietary information, and as such, Haymes Paint cannot be responsible for the content or the accuracy thereof.

Reason(s) for issue : Compositional ingredient/s revised.

Literature References: Model Codes of Practice: Classification and labelling of workplace hazardous chemicals, and

preparation of safety data sheets for hazardous chemicals - Safe Work Australia, July 2020.

Australian Inventory of Industrial Chemicals (AIIC).

European Chemicals Agency (ECHA).

Product name : Ultimate 2 Pack Epoxy Satin White, Tint Bases And Milled Colours (Part A)

Issued: 29-9-22

Version: 2.2 Page 6 of 7



This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Haymes Paint cannot anticipate or control the conditions under which the product may be used, prior to usage, review the SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Product name: Ultimate 2 Pack Epoxy Satin White, Tint Bases And Milled Colours (Part A)

Issued: 29-9-22 Version: 2.2



Hazardous Substance, Non-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product Name Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Product Code: U2ESH

Product Use: Water-based Part B of a two-pack epoxy coating. Also refer to SDS for Part A.

Company Name: Haymes Paint
ABN: 14 004 201 638

Address: Waringa Drive, Wendouree Industrial Park, Victoria 3355, Australia.

Emergency Telephone: 03 5342 6200. Office Hours: 7:30am to 5:30pm Monday to Friday.

Poisons Information Centre : 13 11 26 (From anywhere and anytime in Australia)

Telephone Number/Fax : Tel: 03 5342 6200. Office Hours : 7:30am to 5:30pm Monday to Friday.

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



SIGNAL WORD : Warning

Hazard Classification : Skin Irritation - Catergory 2

Skin Sensitisation - Category 1A Eye Irritation - Category 2A

Hazard Statement(s): H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

Precautionary Statement(s):

Prevention: P102: Keep out of reach of children.

P103: Read label before use.

P261: Avoid breathing fumes, mists, vapours or spray. P262: Do not get in eyes, on skin, or on clothing. P264: Wash contacted areas thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace. P280: Wear protective gloves, protective clothing and eye or face protection.

Response: P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice. P337+P313: If eye irritation persists: Get medical advice.

Product name: Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Issued: 29-9-22

Version: 2.2 Page 1 of 7



Storage: P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container. P403+P235: Store in a well-ventilated place. Keep cool.

Disposal: P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and

containers to landfill.

SUSMP Poisons Schedule: Not Scheduled.

3. COMPOSITION INFORMATION

 Chemical Entity
 CAS NO
 Proportion

 Polyamide resin
 Not disclosed
 30-60 %

 Isopropanol
 67-63-0
 < 10%</td>

 Ingredients determined not to be hazardous :
 Balance

 100%
 100%

4. FIRST AID MEASURES

For advice, contact a doctor or the Poisons Information Centre (Phone Australia 13 11 26).

Inhalation : No first aid measures normally required. However, if inhalation has occurred, and irritation

has developed, remove to fresh air and observe until recovered. If irritation becomes

painful or persists more than about 30 minutes, seek medical advice.

Skin: Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-

20 minutes or until product is removed. Under running water, remove contaminated

clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek

medical attention.

Eye: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15

minutes or until the product is removed, while holding the eyelid(s) open. Take care not to

rinse contaminated water into the unaffected eye or onto the face. Obtain medical

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and give some water to

drink. If symptons develop, or in doubt, contact a Poisons Information Centre or a doctor.

First Aid Facilities : Emergency eye wash facility.

Advice to Doctor: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Hazchem Code : Not Applicable.

Suitable extinguishing media: Not combustible, however, if material is involved in fire use extinguishing media

appropriate to surrounding fire conditions.

Specific hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or

both), fire gases. There is no risk of an explosion from this product under normal

circumstances if it is involved in a fire. Only small quantities of decomposition products are expected from this product at temperatures normally achieved in a fire. This will only occur after heating to dryness. Fire decomposition products from this product may be toxic if

inhaled. Take appropriate protective measures.

Product name: Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Issued: 29-9-22 Version: 2.2

Page 2 of 7



Fire fighting further advice : Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if

risk of exposure to products of decomposition. Prevent any possible contamination of

drains and waterways.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of

vapours. Collect and seal in properly labelled containers or drums for disposal.

Large Spills: Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so.

Avoid accidents, clean up immediately. Wear full protective chemically resistant equipment to prevent skin and eye contamination and the inhalation of any vapours or dust. Work up wind or increase ventilation. Contain - prevent any possible contamination of drains and waterways. Collect and seal in properly labelled containers or drums for disposal. If contamination of drains or waterways has occurred advise local emergency services.

7. HANDLING AND STORAGE

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work

areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product

Storage : Make sure that containers of this product are kept tightly closed. Keep containers dry and

away from water. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further

storage instructions on the label.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control Parameters: No value assigned for this specific product by Safe Work Australia. However, Workplace

Standard(s) for constituent(s) are:

Chemical Entity TWA STEL Carcinogen Catergory Notices

ppm mg/m3 ppm mg/m3

Isopropanol 983 1230 - -

.

As published by Safe Work Australia

TWA - the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15-minute period, which should not be expected at any time during a normal eight-hour workday.

"Sk" Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If directions for use are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Product name: Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Issued : 29-9-22

Version: 2.2 Page 3 of 7



Engineering Controls: Ensure ventilation is adequate and that air concentrations are controlled below quoted

Workplace Exposure Standards. Close with lid when not in use.

Personal

protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES

Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceAmber coloured liquid.Odour:No data re odour.Solubility:Miscible in water.

Specific Gravity (20 degC): 1.0

Relative Vapour Density (air=1): As for water.

Vapour Pressure (20degC): 2.37 kPa at 20°C (water vapour pressure).

Flash Point (degC):

Flammability Limits (%):

Autoignition Temperature (degC):

Not Applicable

Not Applicable

Melting Point/Range (degC): No specific data. Liquid at normal temperatures.

Boiling Point/Range (degC):

pH:

Not Available

Viscosity:

Not Available

Not Available

Not Available

(Typical values only)

N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: This product is unlikely to react or decompose under normal storage conditions.

However, if you have any doubts, contact the supplier for advice on shelf life

properties.

Chemical stability: Stable under normal ambient and anticipated storage and handling conditions of

temperature and pressure.

Hazardous reactions : This product will not undergo polymerisation reactions.

Conditions to avoid : Keep containers tightly closed. Containers should be kept dry.

Incompatible materials :No particular Incompatibilities.

Hazardous decomposition products: This product is likely to decompose only after heating to dryness, followed by

further strong heating. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form hydrogen

chloride gas, other compounds of chlorine.

Product name: Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Issued: 29-9-22 Version: 2.2

Page 4 of 7



11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if material is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute effects:

Inhalation : Available data indicates that this product is not harmful. However product may be mildly

irritating, although unlikely to cause anything more than mild transient discomfort.

Skin contact : Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once

sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become

evident, but all should disappear once exposure has ceased.

Ingestion: This product is a severe eye irritant. Symptoms may include stinging and reddening of eyes

and watering which may become copious. Other symptoms such as swelling of eyelids and blurred vision may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment is likely to

Eye contact: Significant oral exposure is considered to be unlikely. However, this product is an oral

irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure

has ceased.

Acute toxicity:

Inhalation :No information available.Skin contact :No information available.Ingestion :No information available.

Skin corrosion/irritation : This product has been classified as a Catergory 2 Hazard. Causes skin irritation.

Serious eye damage/irritation : This material has been classified as a Category 2A Hazard. Causes serious eye irritation.

Respiratory Sensitisation : No information available.

Skin Sensitisation : This product has been classified as a Category 1A Hazard - skin sensitiser.

Chronic Toxicity:

Mutagenicity:No information available.Carcinogenicity:No information available.Reproductive toxicity:No information available.

Specific target organ toxicity

(single exposure): No information available.

Specific target organ toxicity

(repeat exposure):

No information available.

Aspiration hazard : No information available.

Product name : Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Issued: 29-9-22

Version: 2.2 Page 5 of 7



12. ECOLOGICAL INFORMATION

Avoid contaminating drains and waterways.

Ecotoxicity: Harmful to aquatic organisms, may cause long-term adverse effects to the aquatic

environment.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled dispose in accordance with local, regional, national and international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport : Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport

of Dangerous Goods by Road and Rail". NON DANGEROUS GOODS.

Marine Transport: Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous

Goods Code (IMDG) Code) for transport by sea. NON DANGEROUS GOODS.

Air Transport : Not classified as Dangerous Goods by the criteria of the International Air Transport

Association (IATA) Dangerous Goods Regulations for transport by air. NON DANGEROUS

GOODS.

15. REGULATORY INFORMATION

This product/constituent(s) is/are covered by the following requirements :

This material is hazardous according to health criteria of Safe Work Australia. HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road and Rail". NON DANGEROUS GOODS.

The Standard for the Uniform Scheduling of Medicines and Poisons No. 36.

Not Scheduled.

All the constituents of this product are listed on the Australian Inventory of Industrial Chemicals (AIIC), or exempted.

16. OTHER INFORMATION

This product is not manufactured by Haymes Paint. This Safety Data Sheet is prepared from proprietary information, and as such, Haymes Paint cannot be responsible for the content or the accuracy thereof.

Reason(s) for issue : Product Code change.

Literature References: Model Codes of Practice: Classification and labelling of workplace hazardous chemicals, and

preparation of safety data sheets for hazardous chemicals - Safe Work Australia, July 2020.

Australian Inventory of Industrial Chemicals (AIIC).

European Chemicals Agency (ECHA).

Product name : Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Issued: 29-9-22

Version: 2.2 Page 6 of 7



This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Haymes Paint cannot anticipate or control the conditions under which the product may be used, prior to usage, review the SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Product name : Ultimate 2 Pack Epoxy Satin Hardener (Part B)

Issued: 29-9-22 Version: 2.2